



Power Take Offs		Ref. TF2007AP
CANTER	MO36S5 ; MO36S6 Pneumatic Control	

To apply with Gear Pumps or Piston Pumps

Main Dimensions

A – Air connection
 B – Pump rotation
 C – Option: Electric sensor with mechanical driving Ref. TF2007APS or TF2007APC

(Dimensions in mm)

Main Data	
Continuous Torque (Nm)	150
Intermittent Torque (Nm)	210
Power (at 1000 rpm)	21 cv / 16 kW
Mounting Position	Left
Pump Rotation	Right Hand
Weight (kg)	5,3
PTO internal ratio	1:0,91
Indicative ratio from motor to PTO's output	1:0,43

CTI TF2007AP 1211- 1

ABER is constantly engaged in improving its products and, therefore, reserves itself the right to modify without any further notice the characteristics shown. The gear boxes are in constant change; therefore, ABER is not to be held responsible for any damage resulting from wrong application or application of outdated material.



ABER - Embragens e Comandos Hidráulicos - A. B. LDA
 Rua Francisco de Almeida, Nº 30 – Vila Nova da Telha – 4470 MAIA - Portugal
 Telephone: +351.22.9438070 Fax: +351.22.9420823 e-mail: aber@aber.pt <http://www.aber.pt>