



<b>Power Take Offs</b> Relation 1 : 1,32		Ref. TF5005AMP
<b>VOLVO</b>	R1000 IT ; SR1000 IT ; R1400 IT ; R1700 IT ; SR1400 IT ; SR1700 IT ; SR1900 IT ; SR2000 IT ; SR2400 IT ; SRO2400 IT ; VT1708 IT ; VT2009B IT ; VT2014B IT ; VT2214 IT ; VT2412B IT ; VT2514B IT ; VTO2214B IT ; VTO2514B IT ; VT2814B IT ; VTO2814B IT	

To apply with Gear Pumps or with Piston Pumps

### Main Dimensions

A – Air connection  
 B – Pump rotation  
 C – Option: Electric sensor with mechanical driving Ref. TF5005AMPS or TF5005AMPC  
 1 – Flange  
 2 – Bearing  
 3 – Circlip  
 4 – Adapter shaft VK5005  
 5 – TF4002AMP

**(Dimensions in mm)**

Main Data		
<b>Continuous Torque (Nm)</b>	<b>300</b>	
<b>Intermittent Torque (Nm)</b>	<b>420</b>	
<b>Power (at 1000 rpm)</b>	<b>42 cv / 32 kW</b>	
<b>Mounting Position</b>	<b>Rear</b>	
<b>Pump Rotation</b>	<b>Right Hand</b>	
<b>Weight (kg)</b>	<b>12,5</b>	
<b>PTO internal ratio</b>	<b>1:1,32</b>	
<b>Indicative ratio from motor to PTO's output</b>		
R 1000 IT ; R 1400 IT ; R 1700 IT ; VT1708 IT ; VT2009B IT	.- 1 : 0.920	
SR 1400 IT ; SR 1700 IT ; SR 1900 IT ; VT2014B IT ; VT2214 IT ; VT2514B IT	High: .- 1 : 1.160	Normal: .- 1 : 0.920
SR 2000 IT	High: .- 1 : 1.080	Normal: .- 1 : 0.860
SRO 2400 IT	High: .- 1 : 1.360	Normal: .- 1 : 1.082
VT2412B IT	High: .- 1 : 1.190	Normal: .- 1 : 0.920
VTO2214B IT ; VTO2514B IT	High: .- 1 : 1.448	Normal: .- 1 : 1.160

CTI TF5005AMP 1211-2

ABER is constantly engaged in improving its products and, therefore, reserves itself the right to modify without any further notice the characteristics shown. The gear boxes are in constant change; therefore, ABER is not to be held responsible for any damage resulting from wrong application or application of outdated material.



**ABER - Embraiaçes e Comandos Hidráulicos - A. B. LDA**  
 Rua Francisco de Almeida, Nº 30 – Vila Nova da Telha – 4470 MAIA - Portugal  
 Telephone: +351.22.9438070 Fax: +351.22.9420823 e-mail: [aber@aber.pt](mailto:aber@aber.pt) <http://www.aber.pt>