



<b>Power Take Offs</b> Relation 1 : 1,73		Ref. TF5009AMP
<b>VOLVO</b>	R1000 IT; SR1000 IT; R1400 IT; R1700 IT; SR1400 IT; SR1700 IT; SR1900 IT; SR2000 IT; SR2400 IT; SRO2400 IT; VT1708 IT; VT2009B IT; VT2014B IT; VT2214 IT; VT2412B IT; VT2514B IT; VTO2214B IT; VTO2514B IT; VT2814B IT; VTO2814B IT	

To apply with Gear Pumps or with Piston Pumps

### Main Dimensions

A – Air connection  
 B – Sense of rotation  
 C – Option: Electric sensor with mechanical driving Ref. TF5009AMPS or TF5009AMPC  
 1 – Flange  
 2 – Bearing  
 3 – Circlip  
 4 – Adapter shaft VK5005  
 5 – TF4034AMP

**(Dimensions in mm)**

Main Data	
<b>Continuous Torque (Nm)</b>	<b>350</b>
<b>Intermittent Torque (Nm)</b>	<b>450</b>
<b>Power (at 1000 rpm)</b>	<b>48 cv / 36 kW</b>
<b>Mounting Position</b>	<b>Rear</b>
<b>Pump Rotation</b>	<b>Right Hand</b>
<b>Weight (kg)</b>	<b>16,2</b>
<b>PTO internal ratio</b>	<b>1:1,73</b>
<b>Indicative ratio from motor to PTO's output</b>	
R 1000 IT; R 1400 IT; R 1700 IT; VT1708 IT; VT2009B IT	.- 1 : 1.211
SR 1400 IT; SR 1700 IT; SR 1900 IT; VT2014B IT; VT2214 IT; VT2514B IT	High: .- 1 : 1.522      Normal: .- 1 : 1.211
SR 2000 IT	High: .- 1 : 1.419      Normal: .- 1 : 2.855
SRO 2400 IT	High: .- 1 : 1.782      Normal: .- 1 : 1.419
VT2412B IT	High: .- 1 : 1.562      Normal: .- 1 : 1.211
VTO2214B IT; VTO2514B IT	High: .- 1 : 1.893      Normal: .- 1 : 1.522

CTI TF5009AMP 1211-1

ABER is constantly engaged in improving its products and, therefore, reserves itself the right to modify without any further notice the characteristics shown. The gear boxes are in constant change; therefore, ABER is not to be held responsible for any damage resulting from wrong application or application of outdated material.



**ABER - Embraiaçens e Comandos Hidráulicos - A. B. LDA**  
 Rua Francisco de Almeida, Nº 30 – Vila Nova da Telha – 4470 MAIA - Portugal  
 Telephone: +351.22.9438070 Fax: +351.22.9420823 e-mail: [aber@aber.pt](mailto:aber@aber.pt) <http://www.aber.pt>