



Power Take Offs		Ref. TF5012AMP
Relation 1 : 1,35		
VOLVO	R1000; SR1000; R1400; R1700; SR1400; SR1700; SR1900; SR2000; SR2400; SRO2400; VT1708; VT2009B; VT2014B; VT2214; VT2412B; VT2514B; VTO2214B; VTO2514B; VT2814B; VTO2814B	

To apply with Gear Pumps or with Piston Pumps

Main Dimensions

A – Air connection
 B – Sense of rotation
 C – Option: Electric sensor with mechanical driving Ref. TF5012AMPS or TF5012AMPC
 1 – Flange
 2 – Bearing
 3 – Circlip
 4 – Adapter shaft VK5004
 5 – TF4036AMP

(Dimensions in mm)

Main Data	
Continuous Torque (Nm)	450
Intermittent Torque (Nm)	500
Power (at 1000 rpm)	62 cv / 46 kW
Mounting Position	Rear
Pump Rotation	Right Hand
Weight (kg)	16
PTO internal ratio	1:1,35
Indicative ratio from motor to PTO's output	
R 1000 ; R 1400 ; R 1700 ; VT1708 ; VT2009B	.- 1 : 0.945
SR 1400 ; SR 1700 ; SR 1900 ; VT2014B ; VT2214 ; VT2514B	High: .- 1 : 1.188 Normal: .- 1 : 0.945
SR 2000	High: .- 1 : 1.107 Normal: .- 1 : 2.228
SRO 2400	High: .- 1 : 1.391 Normal: .- 1 : 1.107
VT2412B	High: .- 1 : 1.219 Normal: .- 1 : 0.945
VTO2214B ; VTO2514B	High: .- 1 : 1.477 Normal: .- 1 : 1.188

CTI TF5012AMP 1211-1

ABER is constantly engaged in improving its products and, therefore, reserves itself the right to modify without any further notice the characteristics shown. The gear boxes are in constant change; therefore, ABER is not to be held responsible for any damage resulting from wrong application or application of outdated material.



ABER - Embraiaçes e Comandos Hidráulicos - A. B. LDA
 Rua Francisco de Almeida, Nº 30 – Vila Nova da Telha – 4470 MAIA - Portugal
 Telephone: +351.22.9438070 Fax: +351.22.9420823 e-mail: aber@aber.pt <http://www.aber.pt>