



Power Take Offs Relation 1 : 1		Ref. TF5015SP
VOLVO	AT 2412C; AT 2412AT; AT 2512C; AT 2514; AT 2515C; AT 2812C; ATO 2512C; ATO 3112C	

To apply with Gear pumps or with Piston Pumps

Main Dimensions

A – Air connection
 B – Pump rotation
 C – Option: Electric sensor with mechanical driving Ref. TF5015SPS or TF5015SPC
 1 – Flange
 2 – Bearing
 3 – Circlip
 4 – Adapter shaft VK5006
 5 – TF4002SP

(Dimensions in mm)

Main Data		
Continuous Torque (Nm)	300	
Intermittent Torque (Nm)	420	
Power (at 1000 rpm)	42 cv / 32 kW	
Mounting Position	Rear	
Pump Rotation	Right Hand	
Weight (kg)	7,5	
PTO internal ratio	1:1	
Indicative ratio from motor to PTO's output		
AT 2412C	High: .- 1 : 0.880	Normal: .- 1 : 0.700

CTI TF5015SP 1211 - 5

ABER is constantly engaged in improving its products and, therefore, reserves itself the right to modify without any further notice the characteristics shown. The gear boxes are in constant change; therefore, ABER is not to be held responsible for any damage resulting from wrong application or application of outdated material.



ABER - Embraiaçens e Comandos Hidráulicos - A. B. LDA

Rua Francisco de Almeida, Nº 30 – Vila Nova da Telha – 4470 MAIA - Portugal

Telephone: +351.22.9438070 Fax: +351.22.9420823 e-mail: aber@aber.pt <http://www.aber.pt>