



Power Take Offs Relation 1 : 1,56		Ref. TF5018AMP
VOLVO	AT 2412C; AT 2412AT; AT 2512 C; AT 2514; AT 2515C; AT 2812C; ATO 2512C; ATO 3112C	

To apply with Gear Pumps or with Piston Pumps

Main Dimensions

A – Air connection
 B – Sense of rotation
 C – Option: Electric sensor with mechanical driving Ref. TF5018AMPS or TF5018AMPC
 1 – Flange
 2 – Bearing
 3 – Circlip
 4 – Adapter shaft VK5006
 5 – TF4035AMP

(Dimensions in mm)

Main Data	
Continuous Torque (Nm)	400
Intermittent Torque (Nm)	500
Power (at 1000 rpm)	55 cv / 40 kW
Mounting Position	Rear
Pump Rotation	Right Hand
Weight (kg)	15,3
PTO internal ratio	1:1,56
Indicative ratio from motor to PTO's output	
AT 2412C	High: - 1 : 1.373 Normal: - 1 : 1.092

CTI TF5018AMP 1211-2

ABER is constantly engaged in improving its products and, therefore, reserves itself the right to modify without any further notice the characteristics shown. The gear boxes are in constant change; therefore, ABER is not to be held responsible for any damage resulting from wrong application or application of outdated material.



ABER - Embragens e Comandos Hidráulicos - A. B. LDA

Rua Francisco de Almeida, Nº 30 – Vila Nova da Telha – 4470 MAIA - Portugal

Telephone: +351.22.9438070 Fax: +351.22.9420823 e-mail: aber@aber.pt <http://www.aber.pt>