



Power Take Offs		Ref. TF8017AMP
Relation 1 : 1		
MERCEDES	G210 IT; G211 IT; G221 IT; G240 IT; G248 IT; G260 IT; G131-9 IT; G231-16 IT; G241-16 IT; G330 IT (G125 IT ; G155 IT ; G180 IT ; G200 IT Current flange produced after 1990)	

To apply with Gear Pumps or with Piston Pumps

Main Dimensions

A – Air connection
 B – Sense of rotation
 C – Option: Electric sensor with mechanical driving Ref. TF8017AMPS or TF8017AMPC
 1 – Circlip
 2 – Adapter shaft VK8010
 3 – Bearing
 4 – Flange
 5 – Plate
 6 – TF4033AMP

(Dimensions in mm)

Main Data	
Continuous Torque (Nm)	500
Intermittent Torque (Nm)	550
Power (at 1000 rpm)	69 cv / 51 kW
Mounting Position	Rear
Pump Rotation	Right Hand
Weight (kg)	18
PTO internal ratio	1:1
Indicative ratio from motor to PTO's output	
G210 High: 1 : 1.03 Normal: 1 : 0.85	G260 High: 1 : 1.50 Normal: 1 : 1.24
G211 High: 1 : 0.85 Normal: 1 : 0.71	G131 - 9 / 14.57 1 : 0.743
G221 High: 1 : 0.85 Normal: 1 : 0.71	G125 / G155 / G180 High: 1 : 1.128 Normal: 1 : 0.958
G240 High: 1 : 1.24 Normal: 1 : 1.03	G200 High: 1 : 1.126 Normal: 1 : 0.949

CTI TF8017AMP 1211-1

ABER is constantly engaged in improving its products and, therefore, reserves itself the right to modify without any further notice the characteristics shown. The gear boxes are in constant change; therefore, ABER is not to be held responsible for any damage resulting from wrong application or application of outdated material.



ABER - Embraiaçes e Comandos Hidráulicos - A. B. LDA
 Rua Francisco de Almeida, Nº 30 – Vila Nova da Telha – 4470 MAIA - Portugal
 Telephone: +351.22.9438070 Fax: +351.22.9420823 e-mail: aber@aber.pt <http://www.aber.pt>